



ELECTRO  **TECH'S**

1875 Sampson Ave., Corona, CA 92879
(951) 734-1812 Fax: (951) 734-5424

12K26X10WP

12" Red LED Railroad Crossing Signal With White Side Ports

Specifications

| | |
|---------------------------|---|
| LEDs | High efficiency |
| Operating temperature | -40° C to +75° C |
| Dominant wavelength (nm) | 630 nm |
| Power consumption (W) | 10 W |
| Nominal operating voltage | 10 VAC / VDC (other voltages available) |
| Rated operating voltage | 8-12 VAC / VDC |
| Dimensions | 12" |
| Interconnect | 1/4" ring terminal |
| Housing | Water tight, vented polycarbonate |

Three Element LED Signal

1. Red LED matrix with attached white LED matrices
2. Water tight housing with transparent sideports
3. Red Tinted Polycarbonate Lense (Prismatic and clear available)

Available Now:

- A. **RETROFIT KIT:** Designed to fit into existing systems with handtools.
Installation time and effort is minimal.

| 100,000 Hour * LED Life Expectancy | | | | | | |
|---------------------------------------|----|----|----|----|----|-----|
| YEARS | 22 | 45 | 54 | 68 | 91 | 136 |
| OPERATING HOURS PER DAY | 6 | 5 | 4 | 3 | 2 | 1 |

*50,000 hours for all white LEDs