



ELECTRO  **TECH'S**

1875 Sampson Ave., Corona, CA 92879
(951) 734-1812 Fax: (951) 734-5424

Hand / Man

Specifications

LEDs	High efficiency
Operating temperature	-40° C to +75° C
Dominant wavelength (nm)	See chart below
Power consumption (W)	See chart below
Operating voltage	120 VAC (Other voltages available)
Dimensions	A1 Ped. Bucket
Interconnect	See chart below
Housing	Water Tight

Four Element LED Signal

1. LED matrix
2. Water tight housing
3. Polycarbonate lense
4. Electronic circuitry

Available Now:

Model	Size	Voltage* (VAC)	Wattage (W)	Color	λ (nm)	Screw-base	Flange-mount
HMSXS**	18" X 16" (A1 Ped.)	120	12 / 13	Orange / White	605 / N/A		✓
HMSXS-O***	18" X 16" (A1 Ped.)	120	12 / 9	Orange / White	605 / N/A		✓
HODOTPOR****	11.5" X 7.5"	120	12	Orange	605	✓	
LWMAN*****	11.5" X 7.5"	120	14	White	N/A	✓	

*Other voltages available

**HMSXS – Hand / Man side-by-side by-side, but the man is outlined to cut cost and power consumption

***HMSXS-O – Hand / Man side-

****HODOTPOR – Hand

*****LWMAN - Man